Pt. 82, Subpt. G, App. L

Environmental Protection Agency

APPENDIX K TO SUBPART G OF PART 82—SUBSTITUTES SUBJECT TO USE RESTRIC-TIONS AND UNACCEPTABLE SUBSTITUTES LISTED IN THE JULY 22, 2002, FINAL RULE, EFFECTIVE AUGUST 21, 2002

FOAM BLOWING-UNACCEPTABLE SUBSTITUTES

End-use	Substitute	Decision	Comments					
Replacements for HCFC-141b in the following rigid polyurethane/ polyisocyanurate applications: —Boardstock	HCFC-22, HCFC- 142b and blends thereof.	Unacceptable	Alternatives ODP.	exist	with	lower	or	zero-
—Appliance —Spray All foam end-uses	HCFC-124	Unacceptable	Alternatives ODP.	exist	with	lower	or	zero-

 $[67~{
m FR}~47721,~{
m July}~22,~2002,~{
m as}~{
m amended}~{
m at}~72~{
m FR}~14443,~{
m Mar}.~28,~2007]$

APPENDIX L TO SUBPART G OF PART 82—SUBSTITUTES LISTED IN THE JANUARY 27, 2003, Final Rule, Effective March 28, 2003

FIRE SUPPRESSION AND EXPLOSION PROTECTION SECTOR—TOTAL FLOODING SUBSTITUTES— ACCEPTABLE SUBJECT TO USE CONDITIONS

End-use	Substitute	Decision	Decision Conditions Co	
Total flooding	HFC227-BC	Acceptable subject to use conditions.	Sodium bicarbonate release in all settings should be targeted so that increased pH level would not adversely affect exposed individuals. Users should provide special training to individuals required to be in environments protected by HFC227–BC extinguishing systems. Each HFC227–BC extinguisher should be clearly labelled with the potential hazards from use and safe handling procedures.	Use of the agent, HFC-227ea, should be in accordance with the safety guidelines in the latest edition of the NFPA 2001 Standard for Clean Agent Fire Extinguishing Systems. See additional comments 1, 2, 3, 4, 5.

Additional comments.

Additional comments.

1—Should conform with relevant OSHA requirements, including 29 CFR part 1910, subpart L, sections 1910.160 and 1910.162.

2—Per OSHA requirements, protective gear (SCBA) should be available in the event personnel should reenter the area.

3—Discharge testing should be strictly limited to that which is essential to meet safety or performance requirements.

4—The agent should be recovered from the fire protection system in conjunction with testing or servicing, and recycled for later use or destroyed.

5—EPA has no intention of duplicating or displacing OSHA coverage related to the use of personal protective equipment (e.g., respiratory protection), fire protection, hazard communication, worker training or any other occupational safety and health standard with respect to halon substitutes.